



Schweizerische Eidgenossenschaft  
Confédération suisse  
Confederazione Svizzera  
Confederaziun svizra

Swiss Confederation

Federal Department of Economic Affairs,  
Education and Research EAER  
**State Secretariat for Economic Affairs SECO**  
Swiss Accreditation Service SAS

## SCS Directory

**Accreditation number: SCS 0146**

International standard: ISO/IEC 17025:2017

Swiss standard: SN EN ISO/IEC 17025:2018

EMC PARTNER AG  
Baselstrasse 160  
4242 Laufen

Head: Renato Henz  
Responsible for MS: Daniel Lutz  
Telephone: +41 61 775 20 30  
E-Mail: [service@emc-partner.ch](mailto:service@emc-partner.ch)  
Internet: [www.emc-partner.com](http://www.emc-partner.com)  
Initial accreditation: 30.11.2016  
Current accreditation: 30.11.2021 to 29.11.2026  
Scope of accreditation see: [www.sas.admin.ch](http://www.sas.admin.ch)  
(Accredited bodies)

### Scope of accreditation as of 30.11.2021

#### Calibration laboratory for electrical quantities

Calibration and Measurement Capability (CMC)

On site calibration available on request excepting S-Parameters

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions T <sub>amb</sub> : 18 °C ... 28 °C	Best Measurement Capability ± <sup>1)</sup>	Remarks
DC Voltage V <sub>dc</sub>	1 mV ... 10 mV 10 mV ... 1000 V		0,5 % 0,1 %	Output Voltage of Voltage sources or Test-Generators
DC High V <sub>dc</sub> (by resistive divider)	0,1 KV ... 30 kV		0,8 %	Output Voltage of EMC-Test-Generators and charging voltages of Pulse Circuits, IEC 61000-4-x
AC Voltage V <sub>ac</sub>	1 mV ... 10 mV 10 mV ... 750 V	f = 10 Hz ... 1000 Hz	4,0 % 0,5 %	Output Voltage of Voltage sources or Test-Generators



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18 \text{ }^{\circ}\text{C} \dots 28 \text{ }^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
<b>DC Current <math>I_{DC}</math></b>	1 mA ... 30 A		0,5 %	
<b>AC-Current <math>I_{AC}</math></b>	1 mA ... 3 A	$f = 10 \text{ Hz} \dots 1000 \text{ Hz}$	1,0 %	
	1 A ... 1200 A	$f = 50 \text{ Hz} \dots 1000 \text{ Hz}$	1,5 %	By current clamp
	100 A ... 2000 A	$f = 10 \text{ Hz} \dots 1000 \text{ Hz}$	2,0 %	By Rogowski coil
				Output current of EMC-Test-Generators f. e. acc. to IEC 61000-4-8
<b>Resistance (DC)</b>	0,1 $\Omega$ ... 1 $\Omega$		5,0 %	
	1 $\Omega$ ... 10 $\Omega$		0,5 %	
	10 $\Omega$ ... 1 M $\Omega$		0,1 %	
	1 M $\Omega$ ... 10 M $\Omega$		0,5 %	
	10 M $\Omega$ ... 100 M $\Omega$		1,0 %	
<b>Capacitance C</b>	100 pF ... 10 $\mu\text{F}$	$f = 1 \text{ kHz}$	0,5 %	
	10 $\mu\text{F}$ ... 100 $\mu\text{F}$	$f = 1 \text{ kHz}$	1,0 %	
<b>Inductance L</b>	10 $\mu\text{H}$ ... 100 $\mu\text{H}$	$f = 1 \text{ kHz}$	0,7 %	
	100 $\mu\text{H}$ ... 1 H	$f = 1 \text{ kHz}$	0,5 %	
<b>Frequency f, Sine</b>	10 Hz ... 300 kHz	$V = 0,1 \text{ V} \dots 750 \text{ V}$	0,05 %	
<b>S Parameter</b>				
<b>S21</b> No on site Calibration available	0 dB ... -40 dB	$f = 300 \text{ kHz} \dots 3 \text{ GHz}$	0,27 dB	@ $ S_{11} $ and $ S_{22}  < 0,0316$ (-30 dB)
	-40 dB ... -60 dB		0,39 dB	
	-60 dB ... -80 dB		0,44 dB	
<b>ESD</b>				
Contact discharge on ESD-Target + Attenuator		Relative humidity: 30 % ... 60 %, Air pressure: 86 kPa ... 106 kPa		Acc. to IEC 61000-4-2
<b>Peak current <math>I_{P1}</math></b>	2 A ... 120 A		4,5 % (8 %) *	
<b>Peak current <math>I_{P2}</math></b> between 10 to 40 ns	2 A ... 120 A		6,2 % (16 %) *	
<b>Current <math>I@30 \text{ ns}</math></b>	2 A ... 120 A		6,2 % (16 %) *	* Incl. reproducibility
<b>Current <math>I@60 \text{ ns}</math></b>	2 A ... 120 A		6,2 % (8 %) *	



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18^{\circ}\text{C} \dots 28^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
Current $I@60\text{ ns} \dots 800\text{ ns}$	2 A ... 120 A		6,2 % (8 %) *	
Rise Time $t_r$	500 ps ... 1000 ps		55 ps	
Pulse Width $t_w$ 60 % - 60 %	500 ps ... 3000 ps		110 ps	
<b>EFT</b>				Acc. to IEC 61000-4-4
Peak Voltage	20 V ... 4000 V	Into 50 $\Omega$	3,8 %	
CDN Peak Voltage	20 V ... 4000 V	Into 50 $\Omega$	4,0 %	
Peak Voltage	20 V ... 8000 V	Into 1 k $\Omega$	4,1 %	
Rise Time	1 ns ... 1 $\mu$ s		200 ps	
Pulse Width	10 ns ... 1 $\mu$ s		1000 ps	
CDN Pulse Width	10 ns ... 1 $\mu$ s		900 ps	
Impulse Repetition Time	1 $\mu$ s ... 10 ms		10 ns	
Burst Duration	0,1 ms ... 100 ms		1,0 $\mu$ s	
Burst Period	1 ms ... 1 s		10 $\mu$ s	
<b>EFT-Load 50 <math>\Omega</math></b>				
Input Impedance	10 $\Omega$ ... 100 $\Omega$	DC	0,1 %	
Insertion Loss (60 dB)	50 dB ... 70 dB	$f = 300\text{ kHz} \dots 100\text{ MHz}$	0,30 dB	
		$f = 100\text{ MHz} \dots 400\text{ MHz}$	0,32 dB	
<b>EFT-Load 1 k<math>\Omega</math></b>				
Input Impedance	10 $\Omega$ ... 10 000 $\Omega$	DC	0,1 %	
Insertion Loss (60 dB)	50 dB ... 70 dB	$f = 300\text{ kHz} \dots 100\text{ MHz}$	0,34 dB	
		$f = 100\text{ MHz} \dots 400\text{ MHz}$	0,41 dB	



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18 \text{ }^{\circ}\text{C} \dots 28 \text{ }^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
<b>Surge CWG 1,2/ 50 <math>\mu\text{s}</math></b>				Acc. to IEC 61000-4-5, extended ranges
Peak Voltage	100 V ... 6000 V		2,3 %	
	6 kV ... 25 kV		3,1 %	
Peak Current	20 A ... 6000 A		2,3 %	
	6 kA ... 100 kA		2,6 %	
Front Time (Voltage)	0,8 $\mu\text{s}$ ... 2,5 $\mu\text{s}$	Peak voltage $\leq$ 6 kV	50 ns	
		Peak voltage $>$ 6 kV	60 ns	
Front Time (Current)	0,9 $\mu\text{s}$ ... 9,6 $\mu\text{s}$	20 A ... 6000 A	130 ns	
		6 kA ... 100 kA	150 ns	
Pulse Duration (Voltage)	5 $\mu\text{s}$ ... 60 $\mu\text{s}$	Peak voltage $\leq$ 6 kV	330 ns	
		Peak voltage $>$ 6 kV	3400 ns	
Pulse Duration (Current)	9,1 $\mu\text{s}$ ... 62,4 $\mu\text{s}$	20 A ... 6 kA	200 ns	
	16 $\mu\text{s}$ ... 24 $\mu\text{s}$	6 kA ... 100 kA	220 ns	
Phase angle 50/60 Hz	0° ... 360°		1,0 °	
<b>Surge Telecom 10/700 <math>\mu\text{s}</math></b>				Annex A
Peak Voltage	100 V ... 6000 V		2,3 %	
	6 kV ... 12 kV		2,8 %	
Peak Current	5 A ... 600 A		2,3 %	
Front Time (Voltage)	5,6 $\mu\text{s}$ ... 13 $\mu\text{s}$	Peak voltage $\leq$ 6 kV	230 ns	
		Peak voltage $>$ 6 kV	270 ns	
Front Time (Current)	2 $\mu\text{s}$ ... 6 $\mu\text{s}$		110 ns	
Pulse Duration (Voltage)	175 $\mu\text{s}$ ... 840 $\mu\text{s}$	Peak voltage $\leq$ 6 kV	5 $\mu\text{s}$	
		Peak voltage $>$ 6 kV	20 $\mu\text{s}$	
Pulse Duration (Current)	254 $\mu\text{s}$ ... 384 $\mu\text{s}$	5 A ... 600 A	2,1 $\mu\text{s}$	



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18 \text{ }^{\circ}\text{C} \dots 28 \text{ }^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
<b>Insulation 0,5 Joule</b>				
Peak Voltage	500 V ... 6000 V	Surge 1,2/ 50 $\mu\text{s}$	2,3 %	Acc. to IEC 60060-1 and IEC 60255-26
	6 kV ... 25 kV		3,1 %	
Front Time (Voltage)	0,8 $\mu\text{s}$ ... 2,5 $\mu\text{s}$	Peak Voltage $\leq$ 6 kV	50 ns	
		Peak Voltage $>$ 6 kV	60 ns	
Duration (Voltage)	5 $\mu\text{s}$ ... 60 $\mu\text{s}$	Peak Voltage $\leq$ 6 kV	330 ns	
		Peak Voltage $>$ 6 kV	3400 ns	
Peak Current	0,5 A ... 160 A		3,0 %	
<b>Surge Magnetic Field</b>				Acc. to IEC 61000-4-9
Pulse Duration (Current)	18 $\mu\text{s}$ ... 28 $\mu\text{s}$	100 A ... 1600 A	150 ns	
Front Time (Current)	7,2 $\mu\text{s}$ ... 11,2 $\mu\text{s}$	100 A ... 1600 A	110 ns	
Peak Current	100 A ... 1600 A		2,3 %	
<b>DOW (slow) Magnetic field</b>				Acc. to IEC 61000-4-10
Peak Current	1 A ... 300 A	0,1/ 1 MHz	3,0 %	
5 <sup>th</sup> Current Peak	0,5 A ... 300 A		3,2 %	
10 <sup>th</sup> Current Peak	0,1 A ... 300 A		4,0 %	
Decay Rate	$ I_{pk5}/ I_{pk1}  > 50 \text{ \%}$ $ I_{pk10}/ I_{pk1}  < 50 \text{ \%}$		4,5% 5,0 %	
Oscillation Period	0,8 $\mu\text{s}$ ... 12 $\mu\text{s}$	0,8 A ... 300 A	0,5 %	
Repetition Time of the Impulses	2 ms ... 30 ms		4,0 $\mu\text{s}$	
<b>Ring wave</b>				Acc. to IEC 61000-4-12
Peak Voltage	100 V ... 6000 V		2,4 %	
	6 kV ... 12 kV		2,8 %	
Voltage Decay	$0,4 < \text{Ratio Pk2 to Pk1} < 1,1$	100 V ... 6000 V	4,0 %	
	$0,4 < \text{Ratio Pk3 to Pk2} < 0,8$		4,6 %	
	$0,4 < \text{Ratio Pk4 to Pk3} < 0,8$		7,4 %	



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18 \text{ }^{\circ}\text{C} \dots 28 \text{ }^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
Peak Current	$0,4 < \text{Ratio Pk2 to Pk1} < 1,1$	6 kV ... 12 kV	4,4 %	
	$0,4 < \text{Ratio Pk3 to Pk2} < 0,8$		5,0 %	
	$0,4 < \text{Ratio Pk4 to Pk3} < 0,8$		7,7 %	
Peak Current	7,5 A ... 1000 A		2,8 %	
Rise Time (Voltage)	0,35 $\mu\text{s}$ ... 0,65 $\mu\text{s}$	100 V ... 6000 V 6 kV ... 12 kV	15 ns 20 ns	
Voltage Period 100 kHz	8,2 $\mu\text{s}$ ... 12,5 $\mu\text{s}$	100 V ... 6000 V 6 kV ... 12 kV	0,15 % 0,45 %	
Rise Time (Current)	0,35 $\mu\text{s}$ ... 1 $\mu\text{s}$		20 ns	
Phase Angle 50/ 60 Hz	0° up to 360°		1,0 °	
<b>Voltage dips and interruption</b>				Acc. to IEC 61000-4-11 or IEC 61000-4-34 (High current 16A $< I < 75 \text{ A}$ )
Voltage	10 V ... 1000 V	f = 50/ 60 Hz	2,5 %	
Rise Time/ Fall Time	1 $\mu\text{s}$ ... 5 $\mu\text{s}$		50 ns	
Peak Voltage	-50 V ... +50 V		2,7 %	
Inrush Current	200 A ... 1000 A		3,5 %	
Phase Angle	0 ° up to 360 °		1,0 °	
<b>SLOW DOW</b>		100 kHz/ 1 MHz		Acc. to IEC 61000-4-18
Peak Voltage	200 V ... 5000 V	Open Circuit	3,6 %	
5 <sup>th</sup> Peak Voltage	100 V ... 5000 V	$Z_{oc} \geq 10 \text{ k}\Omega$	3,9 %	
10 <sup>th</sup> Peak Voltage	20 V ... 5000 V		4,6 %	
Decaying (Voltage)	$V_{Pk5} > 50 \% \text{ of } V_{Pk1}$ $V_{Pk10} < 50 \% \text{ of } V_{Pk1}$		5,2 % 5,8 %	
Rise Time	75 ns	60 ... 90 ns	3,5 ns	
T <sub>Period</sub> Voltage	0,8 $\mu\text{s}$ ... 12 $\mu\text{s}$		0,36 %	
Burst Duration	$\geq 2 \text{ s}$		200,0 ns	
Repetition Rate of the Pulses	30/ s ... 500/ s		4,0 $\mu\text{s}$	
Peak Current	0,5 A ... 100 A	$Z_{sc} \leq 0,1 \Omega$	3,0 %	



## SCS Directory

**Accreditation number: SCS 0146**

Measured Quantity / Instrument or Gauge	Measurement Range	Measurement Conditions $T_{amb}: 18 \text{ }^{\circ}\text{C} \dots 28 \text{ }^{\circ}\text{C}$	Best Measurement Capability $\pm^{1)}$	Remarks
<b>FAST DOW</b>		3/ 10/ 30 MHz		Acc. to IEC 61000-4-18
Peak Voltage	200 V ... 5000 V	$Z_{oc} = 1 \text{ k}\Omega$	3,5 %	
5 <sup>th</sup> Peak Voltage	100 V ... 5000 V		5,3%	
10 <sup>th</sup> Peak Voltage	20 V ... 5000 V		5,8 %	
Decaying	$V_{Pk5} > 50 \text{ \% of } V_{Pk1}$ $V_{Pk10} < 50 \text{ \% of } V_{Pk1}$		6,2 % 6,6 %	
Rise Time	3,5 ns ... 6,5 ns	$Z_{oc} = 1 \text{ k}\Omega$	0,22 ns	
Period	25 ns ... 450 ns		0,5%	
Burst Duration	4 ms ... 100 ms		5,0 $\mu\text{s}$	
Repetition Rate	0,18 ms ... 0,22 ms		50,0 ns	
Peak Current	1,0 A ... 100 A	$Z_{sc} = 0,1 \text{ }\Omega \pm 2 \text{ \%}$	3,0 % ... 4,9%	Depending on frequency
5 <sup>th</sup> Peak Current	0,25 A ... 100 A		4,4 % ... 6,1%	
10 <sup>th</sup> Peak Current	0,1 A ... 100 A		6,2 % ... 7,9%	
Decaying	$I_{Pk5} > 25 \text{ \% of } I_{Pk1}$ $I_{Pk10} < 25 \text{ \% of } I_{Pk1}$		5,2 % ... 7,6 % 6,9 % ... 9,2 %	Depending on frequency
Rise Time	3,5 ns ... 450 ns		1,0 ns	

\* / \* / \* / \* / \*